

View Online at <https://aerobasegroup.com/nsn/5935-00-755-2912>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Wall type w/ or w/o cover

Overall Length:

4.562 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.271 inches and 3.291 inches

Overall Height:

Between 1.530 inches and 1.590 inches

Overall Width:

2.812 inches

Environmental Protection:

Moisture proof

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 5-15" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Thread Length:

0.875 inches

Thready Qty Per Inch (tpi):

32 and 32

Thread Size:

0.138 inches and 0.164 inches

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Flat socket single mating end 2nd contact grouping

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0