

View Online at <https://aerobasegroup.com/nsn/5935-00-755-2912>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Wall type w/ or w/o cover

**Overall Length:**

4.562 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 3.271 inches and 3.291 inches

**Overall Height:**

Between 1.530 inches and 1.590 inches

**Overall Width:**

2.812 inches

**Environmental Protection:**

Moisture proof

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"3, 5-15" single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Thread Length:**

0.875 inches

**Thready Qty Per Inch (tpi):**

32 and 32

**Thread Size:**

0.138 inches and 0.164 inches

**Terminal Location:**

Side single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Screw single mating end all contact groupings

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

2 single mating end 2nd contact grouping

**Included Contact Type:**

Flat socket single mating end 2nd contact grouping

**Thread Series Designator:**

Unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0