

View Online at <https://aerobasegroup.com/nsn/5935-00-755-3164>

Thread Class:

2a and 2a

Body Style:

Straight shape threaded

Overall Length:

Between 1.631 inches and 1.652 inches

Overall Diameter:

Between 2.865 inches and 2.886 inches

Environmental Protection:

Explosion proof and moisture resistant

Distance From Mounting Shoulder To Front Face:

1.329 inches

Mounting Facility Thickness:

Between 0.094 inches and 0.328 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

10 and 16

Thread Size:

2.250 inches and 2.375 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

40 single mating end 2nd contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end 2nd contact grouping

Thread Series Designator:

Double stub and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0