NSN 5935-00-755-3550



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-755-3550 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.800 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.593 inches **Overall Height:** 0.840 inches **Overall Width:** 1.080 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.468 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 34 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid Thready Qty Per Inch (tpi): **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass and plastic diallyl phthalate single mating end

NSN 5935-00-755-3550

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-p-19833, ty gdi-30 military specification all material responses single mating end
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.034 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-p-19833 spec.