

View Online at <https://aerobasegroup.com/nsn/5935-00-755-5175>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.703 inches

Overall Diameter:

1.438 inches

Environmental Protection:

Hermetic

Distance From Mounting Shoulder To Front Face:

0.250 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

21-30 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

2400.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 6

Thread Size:

1.250 inches and 1.312 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Steel single mating end all contact groupings

Contact Surface Treatment:

Cadmium single mating end all contact groupings

Insert Material:

Glass single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Steel

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

3 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

Solder flange mtd

Thread Series Designator:

Unef and special acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A039b0