Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-755-5296

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.576 inches
Overall Diameter:
1.875 inches
Environmental Protection:
Salt water resistant and vibration proof
Distance From Mounting Shoulder To Front Face:
1.156 inches
Mounting Facility Thickness:
0.235 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
22-22 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
46.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
450.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.375 inches and 1.375 inches

## NSN 5935-00-755-5296 Electrical Receptacle Connector - Page 2 of 2

AeroBase Group

**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Rubber chloroprene class cr single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 4 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.020 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0