NSN 5935-00-755-9674

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-755-9674 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.200 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.800 inches **Overall Height:** 0.437 inches **Overall Width:** 1.031 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1765.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 2870.0 single mating end single contact grouping **Connector Locking Method:** Friction **Features Provided:** Pre-tinned terminal Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

NSN 5935-00-755-9674

Electrical Receptacle Connector - Page 2 of 2



insert material:
Plastic single mating end and mica single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Plastic
Insert Material Specification:
Mil-m-14, type mfe military specification all material responses single mating end
Included Contact Quantity:
11 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.011 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.