NSN 5935-00-756-7033

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-756-7033 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape **Overall Length:** Between 2.307 inches and 2.317 inches **Overall Height:** Between 0.851 inches and 0.861 inches **Overall Width:** Between 0.745 inches and 0.755 inches **Environmental Protection:** Moisture resistant and vibration resistant and pressure proof **Distance Between Mounting Facility Centers:** Between 1.992 inches and 2.008 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 15 **Contact Position Arrangement Style:** 42 single mating end **Polarization Method:** Jackscrew and polarization boss **Connector Locking Method:** Jackscrew-socket and friction **Thread Size:** 0.138 inches and 0.138 inches and 0.112 inches **Insert Material:** Plastic diallyl phthalate single mating end and silicon single mating end **Insert Material Specification:** Mil-p-19833, type gdi-30f military specification single material response single mating end **Thread Series Designator:** Unc and unc and unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A039b0

NSN 5935-00-756-7033

Electrical Receptacle Connector Body - Page 2 of 2



Mil-std (military Standard):

Mil-p-19833 spec.