## NSN 5935-00-756-9632

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-756-9632

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

Between 2.047 inches and 2.079 inches

**Overall Diameter:** 

Between 1.359 inches and 1.391 inches

**Distance From Mounting Shoulder To Front Face:** 

1.313 inches

**Mounting Facility Thickness:** 

0.125 inches

**Threaded Device Type:** 

Coupling facility and mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

Thready Qty Per Inch (tpi):

20 and 20

**Thread Size:** 

1.000 inches and 1.000 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Insert Material:** 

Plastic polyamide single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Shell Material:** 

Steel comp 303

**Shell Material Specification:** 

Mil-s-7720, cond a military specification single material response

**Included Contact Quantity:** 

1 single mating end single contact grouping

## NSN 5935-00-756-9632

Electrical Receptacle Connector - Page 2 of 2



<b>Bushing Accommodation Hole Shape:</b>
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-s-7720 spec.