NSN 5935-00-758-2905

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-758-2905 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/flange **Overall Length:** Between 2.110 inches and 2.140 inches **Overall Height:** Between 2.230 inches and 2.270 inches **Overall Width:** Between 2.230 inches and 2.270 inches **Unthreaded Mounting Hole Diameter:** Between 0.171 inches and 0.177 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.745 inches and 1.755 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.745 inches and 1.755 inches **Distance From Mounting Shoulder To Front Face:** Between 0.975 inches and 0.985 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 32-17 all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 80.0 all mating ends single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 all mating ends single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 all mating ends single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 45.0 and 315.0 Shell Type: Solid **Connector Locking Method:**

Externally threaded shell

NSN 5935-00-758-2905

Connector Adapter - Page 2 of 2



Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
10
Thread Size:
2.000 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping and silver all mating ends single contact grouping
Insert Material:
Rubber all mating ends
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
4 all mating ends single contact grouping
Included Contact Type:
Round socket 2nd mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.040 gold grains, troy and 0.040 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Double stub
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0