

View Online at <https://aerobasegroup.com/nsn/5935-00-758-3583>

**Thread Class:**

2a and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.812 inches

**Overall Diameter:**

0.375 inches

**Environmental Protection:**

Moisture resistant and pressure proof and vibration resistant and salt water resistant

**Distance From Mounting Shoulder To Front Face:**

0.500 inches

**Mounting Facility Thickness:**

0.188 inches

**Threaded Device Type:**

Coupling facility and coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

36 and 36 and 36

**Thread Size:**

0.190 inches and 0.190 inches and 0.250 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and nickel all mating ends single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Gold and nickel

**Included Contact Quantity:**

2 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contacts and body surface gold

**Precious Material And Weight:**

0.110 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and uns and uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0