

View Online at <https://aerobasegroup.com/nsn/5935-00-758-3583>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.812 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Moisture resistant and pressure proof and vibration resistant and salt water resistant

Distance From Mounting Shoulder To Front Face:

0.500 inches

Mounting Facility Thickness:

0.188 inches

Threaded Device Type:

Coupling facility and coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

36 and 36 and 36

Thread Size:

0.190 inches and 0.190 inches and 0.250 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and nickel all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Gold and nickel

Included Contact Quantity:

2 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contacts and body surface gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0