NSN 5935-00-758-4865

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-758-4865 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, flange mount, external coupling **Overall Length:** 1.360 inches **Overall Height:** 1.531 inches **Overall Width:** 1.531 inches **Environmental Protection:** Moisture proof and pressure proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.156 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-00-758-4865

A039b0

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Potting type
Thread Length:
0.625 inches
Thread Size:
1.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
13 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.013 gold grains, troy and 0.013 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: