## NSN 5935-00-759-0853

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-759-0853

Inread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.698 inches
Overall Diameter:
0.500 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Tnc all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 all mating ends single contact grouping
Thready Qty Per Inch (tpi):
28
Thread Size:
0.438 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:
Plastic tetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 2 military specification single treatment response all mating ends single contact grouping
Contact Material Specification:
Qq-c-530, comp ht federal specification single material response all mating ends single contact grouping
Shell Material:
Steel comp 303

## NSN 5935-00-759-0853

Connector Adapter - Page 2 of 2



Shell Surface Treatment:
Passivate
Shell Material Specification:
Qq-s-763, cl 303 federal specification single material response
Included Contact Quantity:
1 all mating ends single contact grouping
Included Contact Type:
Coaxial socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.