NSN 5935-00-759-0854

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-759-0854

view Offilite at https://defobasegroup.com/nsi//0900-709-000-4
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 1.915 inches and 1.925 inches
Environmental Protection:
Moisture resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Tnc all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Size:
0.438 inches
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:
Plastic polytetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response all mating ends single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response all mating ends single contact grouping
Shell Material:
Steel comp 303
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

Shell Material Specification:

Qq-s-763, class 303, conda federal specification single material response

NSN 5935-00-759-0854

Connector Adapter - Page 2 of 2



Insert Material Specification: Mil-p-19468 military specification single material response all mating ends **Included Contact Quantity:** 2 all mating ends single contact grouping **Included Contact Type:** Coaxial pin all mating ends single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.010 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.