# NSN 5935-00-759-0854

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-759-0854

## Thread Class:

2b

**Thread Direction:** 

Right-hand

### Body Style:

Straight shape, internal coupling

### **Overall Length:**

Between 1.915 inches and 1.925 inches

### **Environmental Protection:**

Moisture resistant and vibration resistant

### Threaded Device Type:

Coupling facility

Mating End Quantity:

2

**Contact Position Arrangement Style:** 

Tnc all mating ends

### Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thread Size:

0.438 inches

**Contact Material:** 

Copper alloy all mating ends single contact grouping

# **Contact Surface Treatment:**

Gold all mating ends single contact grouping

# Insert Material:

Plastic polytetrafluoroethylene all mating ends

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

# Shell Material:

Steel comp 303

# Shell Surface Treatment:

Passivate

# Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Shell Material Specification:

Qq-s-763, class 303, conda federal specification single material response

# NSN 5935-00-759-0854

Connector Adapter - Page 2 of 2



**Insert Material Specification:** 

Mil-p-19468 military specification single material response all mating ends

### Included Contact Quantity:

2 all mating ends single contact grouping

### Included Contact Type:

Coaxial pin all mating ends single contact grouping

### Precious Material And Location:

Contact surface gold

### **Precious Material And Weight:**

0.010 gold grains, troy

### **Precious Material:**

Gold

### **Thread Series Designator:**

Unef

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

### A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.