Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-760-0643

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 6.500 inches and 6.520 inches

Overall Height:

1.010 inches

Overall Width:

Between 0.493 inches and 0.507 inches

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.120 inches

Distance Between Mounting Facility Centers:

Between 6.183 inches and 6.197 inches

Board Accommodated Length:

5.393 inches single board and 5.407 inches single board

Board Accommodated Width:

Between 0.193 inches and 0.207 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

56 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold



Precious Material And Weight:

0.056 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.