## NSN 5935-00-760-3102

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-760-3102

Body Style:
Straight shape threaded
Overall Length:
0.710 inches
Overall Diameter:
1.446 inches
Environmental Protection:
Hermetic and moisture resistant and salt water resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
0.560 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Metal ferrous single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1 or 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Metal ferrous
Shell Surface Treatment:
Tin
Shell Surface Treatment Specification:
Mil-t-10727 military specification single treatment response

**Included Contact Quantity:** 

55 single mating end single contact grouping

## NSN 5935-00-760-3102

Electrical Receptacle Connector - Page 2 of 2



<b>Bushing Accommodation Hole Shape:</b>
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - solder
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.