

View Online at <https://aerobasegroup.com/nsn/5935-00-760-5116>

**Body Style:**

Straight edge type w/card guide

**Overall Length:**

3.006 inches

**Overall Width:**

0.531 inches

**Unthreaded Mounting Hole Diameter:**

0.128 inches

**Distance Between Mounting Facility Centers:**

2.734 inches

**Board Accommodated Length:**

2.415 inches single board

**Board Accommodated Width:**

Between 0.072 inches and 0.077 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750, comp a, spring federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:**

23 single mating end single contact grouping

**Included Contact Type:**

Hermaphrodite single mating end single contact grouping

**Special Features:**

Polarizing pin located at contact position 19

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.023 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.