NSN 5935-00-761-3043

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-761-3043

Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
2.040 inches
Overall Diameter:
1.156 inches
Environmental Protection:
Moisture resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
14-15 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet shell
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:

Cadmium

NSN 5935-00-761-3043

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2 federal specification single treatment response

Included Contact Quantity:

14 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.015 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0