NSN 5935-00-761-3683

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-761-3683 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.870 inches **Overall Height:** 0.470 inches **Overall Width:** 0.230 inches **Distance Between Mounting Facility Centers:** 0.625 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Screw lock pin **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:**

Included Contact Type:

Round pin single mating end single contact grouping

7 single mating end single contact grouping

NSN 5935-00-761-3683

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.007 gold grains, troy and 0.007 silver grains, troy Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:

Demilitarization:

No Fiig: A039b0