NSN 5935-00-761-4494

Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-761-4494

Thread Class: 2b **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling w/backshell **Overall Length:** 1.531 inches **Overall Diameter:** 1.156 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** 14s-2 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end

NSN 5935-00-761-4494 Electrical Plug Connector - Page 2 of 2



older well single mating end single contact grouping	
hell Material:	
luminum alloy	
hell Surface Treatment:	
admium	
hell Surface Treatment Specification:	
q-p-416, type 2, class 3 federal specification single treatment re	esponse
cluded Contact Quantity:	
single mating end single contact grouping	
cluded Contact Type:	
ound socket single mating end single contact grouping	
recious Material And Location:	
ontact surfaces gold and contact surfaces silver	
recious Material And Weight:	
.020 gold grains, troy and 0.020 silver grains, troy	
recious Material:	
old and silver	
hread Series Designator:	
nef	
helf Life:	
/a	
nit Of Measure:	
emilitarization:	
0	
lig:	
039b0	