NSN 5935-00-761-4507

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-761-4507

Body Style: Straight edge type **Overall Length:** 3.006 inches **Overall Height:** 0.453 inches **Overall Width:** 0.531 inches **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** 2.734 inches **Board Accommodated Length:** 2.415 inches single board **Board Accommodated Width:** 0.062 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a, spring federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:**

23 single mating end single contact grouping

NSN 5935-00-761-4507

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.023 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.