

View Online at <https://aerobasegroup.com/nsn/5935-00-761-7721>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, latching

**Overall Length:**

0.906 inches

**Bushing Diameter:**

0.875 inches

**Overall Width:**

1.219 inches

**Diameter:**

1.125 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

10-98 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

4000.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Latching ring

**Thread Length:**

0.219 inches

**Thread Size:**

0.875 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end or plastic melamine single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sdi-5 military specification 1st material response single mating end or mil-m-14, type mme military specification 2nd material response single mating end

**Included Contact Quantity:**

6 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold and contact surface silver

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.