## NSN 5935-00-762-0436

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-762-0436 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.811 inches **Overall Height:** 1.093 inches **Overall Width:** 1.093 inches **Unthreaded Mounting Hole Diameter:** 0.147 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 2000.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 0.688 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** 

Gold single mating end single contact grouping Insert Material:

Plastic single mating end

## NSN 5935-00-762-0436

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0