Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-762-2419

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.093 inches
Overall Diameter:
Between 1.365 inches and 1.385 inches
Environmental Protection:
Watertight
Distance From Mounting Shoulder To Front Face:
Between 0.802 inches and 0.822 inches
Mounting Facility Thickness:
Between 0.094 inches and 0.204 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
16s-8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
1.000 inches and 1.000 inches
Terminal Location:
Back single mating end single contact grouping

NSN 5935-00-762-2419

Electrical Receptacle Connector - Page 2 of 2



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 5 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Furnished items - preformed packing **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.005 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0