

View Online at <https://aerobasegroup.com/nsn/5935-00-762-3231>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Length:

1.157 inches

Overall Diameter:

0.875 inches

Environmental Protection:

Pressure proof and salt water resistant and watertight

Cable Entrance Diameter:

Between 0.142 inches and 0.152 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Ceramic single mating end

Shell Material:

Copper alloy

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0