NSN 5935-00-762-3817

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-762-3817 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Wall type **Overall Height:** 1.219 inches **Overall Width:** 1.719 inches **Body Length:** 2.688 inches **Distance Between Mounting Facility Centers:** 3.281 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 4 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 30.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end all contact groupings **Polarization Method:** Contact **Connector Locking Method:** Shell twistlock **Thread Size:** 0.138 inches **Terminal Location:** Side single mating end all contact groupings **Contact Material:** Copper single mating end all contact groupings **Contact Surface Treatment:**

Gold single mating end all contact groupings

Insert Material:

Plastic single mating end

NSN 5935-00-762-3817

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Ams 2422 assn standard single treatment response single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

3 single mating end 2nd contact grouping

Precious Material And Location:

C0ntact surfaces gold

Precious Material And Weight:

0.004 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0