Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-762-3875

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling w/strain relief |
| Body Length: |
| 2.094 inches |
| Overall Diameter: |
| 1.047 inches |
| Environmental Protection: |
| Watertight |
| Cable Entrance Diameter: |
| 0.234 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Wk-4 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 10.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 0.875 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| |

NSN 5935-00-762-3875

Electrical Plug Connector - Page 2 of 2



Insert Material:

Plastic melamine single mating end or plastic phenolic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.004 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Special acme

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0