NSN 5935-00-762-7338

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-762-7338 **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.203 inches **Overall Diameter:** 1.828 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 61 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Ball **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:**

Cadmium

Included Contact Quantity:

61 single mating end single contact grouping

NSN 5935-00-762-7338

Electrical Plug Connector - Page 2 of 2



I	Incl	hul	ed	Co	ntac	:t]	Γνη	۵.
ı		ıuu	cu	-	IILAV	<i>-</i> L	V	₹.

Round pin single mating end single contact grouping

Special Features:

Polarization position w

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.061 gold grains, troy and 0.061 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0