## NSN 5935-00-762-7338

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-762-7338 **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.203 inches **Overall Diameter:** 1.828 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 61 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Ball **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Cadmium

**Included Contact Quantity:** 

61 single mating end single contact grouping

## NSN 5935-00-762-7338

Electrical Plug Connector - Page 2 of 2



I	Incl	hul	ed	Co	ntac	:t ]	Γνη	۵.
ı		ıuu	cu	-	IILAV	<i>-</i> L	V	₹.

Round pin single mating end single contact grouping

**Special Features:** 

Polarization position w

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.061 gold grains, troy and 0.061 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0