## NSN 5935-00-763-7274

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-763-7274

**Overall Length:** 

Between 2.297 inches and 2.327 inches

**Overall Height:** 

1.352 inches

Overall Width:

Between 1.110 inches and 1.140 inches

**Unthreaded Mounting Hole Diameter:** 

0.136 inches

**Distance Between Mounting Facility Centers:** 

2.062 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

67 single mating end

**Contact Removability:** 

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end 2nd contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Crimp single mating end all contact groupings

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Insert Material Specification:** 

Mil-m-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:** 

64 single mating end 2nd contact grouping

**Included Contact Type:** 

Round pin single mating end all contact groupings

## NSN 5935-00-763-7274

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.067 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.067 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

No

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.