

View Online at <https://aerobasegroup.com/nsn/5935-00-763-7802>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.406 inches and 1.471 inches

Overall Diameter:

Between 1.615 inches and 1.635 inches

Environmental Protection:

Corrosion resistant and moisture resistant and thermal shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.906 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

16-07 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

23.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

225.0 and 190.0 and 160.0 and 50.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

28 and 20

Thread Size:

0.500 inches and 0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium and nickel

Shell Material Specification:

Qq-a-367 federal specification single material response

Insert Material Specification:

Mil-m-14f, type sgd-f military specification single material response single mating end

Included Contact Quantity:

7 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round keyed

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.