NSN 5935-00-763-8205

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-763-8205

View Online at https://aerobasegroup.com/nsn/5935-00-763-8205	1
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, internal coupling	
Overall Length:	
Between 0.927 inches and 0.947 inches	
Overall Diameter:	
Between 1.205 inches and 1.225 inches	
Environmental Protection:	
Moisture resistant and salt water resistant and vibration resistant	
Threaded Device Type:	
Back shell	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
14-37 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
35.0 and 140.0 and 205.0 and 275.0	
Shell Type:	
Solid	
Connector Locking Method:	
Spring friction	
Thready Qty Per Inch (tpi):	
28	
Thread Size:	
0.875 inches	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Terminal Type:	
Crimp single mating end single contact grouping	
Shell Material:	
Aluminum alloy 6061	

NSN 5935-00-763-8205Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Chromium
Shell Material Specification:
Qq-a-367, t6 federal specification single material response
ncluded Contact Quantity:
37 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jn
Specification Data:
31349-mil-c-81511/56 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A039b0