NSN 5935-00-763-8990

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-763-8990 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/cable clamp **Overall Length:** 1.125 inches **Bushing Diameter:** 0.500 inches **Overall Height:** 0.688 inches **Overall Width:** 0.688 inches **Unthreaded Mounting Hole Diameter:** 0.099 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Distance From Mounting Shoulder To Front Face:** 0.547 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut **Thread Size:** 0.437 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-00-763-8990

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Silver **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and shell surfaces silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.005 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef **Shelf Life:** N/a **Unit Of Measure: Demilitarization:** No Fiig: A039b0