

View Online at <https://aerobasegroup.com/nsn/5935-00-764-2333>

Body Style:

Straight edge type w/card guide

Overall Length:

2.406 inches

Overall Height:

0.828 inches

Overall Width:

0.531 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

2.134 inches

Board Accommodated Length:

1.920 inches single board

Board Accommodated Width:

0.125 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

2000.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14f, type sdgf military specification single material response single mating end

Included Contact Quantity:

17 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.017 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.