

View Online at https://aerobasegroup.com/nsn/5935-00-765-6603

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
1.531 inches
Overall Diameter:
Between 1.990 inches and 2.010 inches
Environmental Protection:
Watertight
Distance From Mounting Shoulder To Front Face:
Between 1.209 inches and 1.229 inches
Mounting Facility Thickness:
Between 0.094 inches and 0.360 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
24-21 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
46.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.500 inches and 1.500 inches



Terminal Location: Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold and silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 9 single mating end 2nd contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end all contact groupings **Special Features:** Furnished items - preformed packing **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.014 gold grains, troy and 0.014 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0