

View Online at <https://aerobasegroup.com/nsn/5935-00-767-0651>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.130 inches

Bushing Diameter:

Between 0.480 inches and 0.520 inches

Overall Height:

Between 1.230 inches and 1.270 inches

Overall Width:

Between 1.230 inches and 1.270 inches

Unthreaded Mounting Hole Diameter:

Between 0.136 inches and 0.146 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.873 inches and 0.877 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.873 inches and 0.877 inches

Distance From Mounting Shoulder To Front Face:

Between 0.700 inches and 0.740 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping

Insert Material:

Rubber synthetic single mating end

Contact Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-c-530, cond 1/2 hard federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Tin

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-t-10727 spec.