## NSN 5935-00-767-3407

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-767-3407

**Body Style:** Straight shape threaded **Overall Length:** 0.594 inches Overall Diameter: 0.375 inches **Distance From Mounting Shoulder To Front Face:** 0.370 inches **Mating End Quantity: Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold and copper **Shell Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response **Included Contact Quantity:** 

1 single mating end single contact grouping

### **Bushing Accommodation Hole Shape:**

Round keyed

#### **Included Contact Type:**

Coaxial socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surface gold and shell surface gold

# NSN 5935-00-767-3407

Electrical Receptacle Connector - Page 2 of 2



| Precious Material:           |
|------------------------------|
| Gold                         |
| Shelf Life:                  |
| N/a                          |
| Unit Of Measure:             |
|                              |
| Demilitarization:            |
| No                           |
| Fiig:                        |
| A039b0                       |
| Mil-std (military Standard): |

Mil-g-45204 spec.