

View Online at <https://aerobasegroup.com/nsn/5935-00-768-2602>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.825 inches

**Overall Height:**

Between 1.234 inches and 1.266 inches

**Overall Width:**

Between 1.234 inches and 1.266 inches

**Unthreaded Mounting Hole Diameter:**

0.109 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.938 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.462 inches and 0.472 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

12-10 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Gold

**Shell Surface Treatment:**

Anodize

**Included Contact Quantity:**

10 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface and shell gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0