NSN 5935-00-770-3526

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-770-3526 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.000 inches **Overall Diameter:** 0.810 inches **Environmental Protection:** Moisture resistant and pressure proof and vibration resistant **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell

Thread Length:

0.380 inches

Thread Size:

0.500 inches and 0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Steel single mating end single contact grouping

Contact Surface Treatment:

Tin single mating end single contact grouping

Insert Material:

Ceramic single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Shell Material:

Steel

NSN 5935-00-770-3526

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Tin
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unf and unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fija:

A039b0