## NSN 5935-00-770-3545

Body Style:
Straight type
Overall Length:
4.344 inches
Overall Height:
0.375 inches
Overall Width:
0.485 inches

0.116 inches

**Environmental Protection:** 

Shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

**Distance Between Mounting Facility Centers:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-770-3545

4.030 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Inter-contact polarizing keys
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-p-19833, type gdi-30 military specification single material response single mating end
Included Contact Quantity:
28 single mating end single contact grouping
Included Contact Type:
Bifurcated accordian leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver

## NSN 5935-00-770-3545

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.028 gold grains, troy and 0.028 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-p-19833 spec.