Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-771-6850

Thread Class:
2a
Thread Direction:
Right-hand
Overall Height:
1.625 inches
Overall Width:
1.625 inches
Environmental Protection:
Watertight
Unthreaded Mounting Hole Diameter:
Between 0.175 inches and 0.181 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.620 inches and 0.630 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.620 inches and 0.630 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18
Thread Size:
1.375 inches
Insert Material:
Rubber single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
5 single mating end single contact grouping



Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0