## NSN 5935-00-772-0484

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-772-0484 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.479 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Environmental Protection:** Corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.150 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-10 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 41.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

## NSN 5935-00-772-0484

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
20 and 20
Thread Size:
0.875 inches and 1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.003 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No

Fiig: A039b0