Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-772-0496

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Overall Height:	
1.094 inches	
Body Length:	
1.479 inches	
Body Width:	
1.094 inches	
Environmental Protection:	
Pressure proof and watertight	
Unthreaded Mounting Hole Diameter:	
0.150 inches	
Center To Center Distance Between Mounting Facilities Parallel To Heigh	ht.
0.812 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body W	lidth-
0.812 inches	iutii.
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
41.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
900.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
1250.0 single mating end single contact grouping	
Connector Locking Method:	
Externally threaded shell	
Thready Qty Per Inch (tpi):	
20	
Thread Size:	
0.750 inches	
Insert Material:	
Rubber single mating end	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Anodize	

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0