NSN 5935-00-772-2224

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-772-2224 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.470 inches and 1.612 inches **Overall Height:** Between 1.271 inches and 1.291 inches **Overall Width:** Between 1.271 inches and 1.291 inches **Environmental Protection:** Moisture resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.148 inches and 0.154 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.964 inches and 0.974 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.964 inches and 0.974 inches **Distance From Mounting Shoulder To Front Face:** Between 0.750 inches and 0.766 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thread Length: 0.625 inches

Thread Size: 1.000 inches

NSN 5935-00-772-2224

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.005 gold grains, troy and 0.005 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0