

View Online at <https://aerobasegroup.com/nsn/5935-00-772-2348>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.542 inches

Overall Height:

Between 1.261 inches and 1.301 inches

Overall Width:

Between 1.261 inches and 1.301 inches

Environmental Protection:

Moisture resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

Between 0.148 inches and 0.154 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.964 inches and 0.974 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.964 inches and 0.974 inches

Distance From Mounting Shoulder To Front Face:

Between 0.750 inches and 0.766 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-12 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

80.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thread Size:

0.875 inches and 1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Mod.60

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.005 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A039b0