# NSN 5935-00-772-4927

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-772-4927

Body Style:
Straight type
Overall Length:
1.625 inches
Overall Height:
0.375 inches
Overall Width:
0.188 inches
Environmental Protection:
Heat resistant and corrosion resistant and humidity resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.089 inches
Distance Between Mounting Facility Centers:
1.400 inches
Board Accommodated Length:
1.188 inches single board
Board Accommodated Width:
0.082 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping

# NSN 5935-00-772-4927

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

## **Included Contact Quantity:**

11 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

0.011 gold grains, troy and 0.011 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.