

View Online at <https://aerobasegroup.com/nsn/5935-00-772-5332>

**Body Style:**

Straight shape, external coupling strain relief

**Overall Height:**

1.578 inches

**Overall Width:**

1.578 inches

**Body Length:**

2.200 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Cable Entrance Diameter:**

0.750 inches

**Distance From Mounting Shoulder To Front Face:**

0.556 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

26 number 20 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Insert Material:**

Rubber synthetic single mating end

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

6 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.032 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0