

View Online at <https://aerobasegroup.com/nsn/5935-00-773-1744>

Overall Length:

Between 2.292 inches and 2.332 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.062 inches

Overall Height:

Between 0.985 inches and 1.015 inches

Overall Width:

Between 1.110 inches and 1.145 inches

Environmental Protection:

Moisture resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end 3rd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

800.0 single mating end 2nd contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Radio Frequency Type Contact Characteristic Impedance In Ohms:

75.0 single mating end 2nd contact grouping

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Insert Material Specification:

Mil-m-14, ty mme military specification single material response single mating end

Included Contact Quantity:

29 single mating end 3rd contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.040 gold grains, troy and 0.040 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.